

Contact —



# Edge finders optical






www.ymttooling.co.uk (\*) 01935 428375 opt 3 (\*) tooling@ymtltd.co.uk (\*)

- 20

Made in Germany **YMT Technologies Ltd** Tuscan House, George Smith Way Lufton Trading Estate, Yeovil, Somerset BA22 8QR

# \_\_\_\_\_ precise. pioneering. worldwide.-





precise. pioneering. worldwide. -



# – Edge finders optical 3D –

# Edge finders optical 3D



# Edge finder 3D: developed by us -- produced only by us.





### Function:

If a conductive workpiece and the probing ball touch (within the axis X, Y and Z), the electrical circuit gets closed and a LED signal appears.

When the LED signal appears, the workpiece's edge is reached with a distance of 5 mm (= radius of probing ball Ø10).

In Z axis, the reference length has to be measured and taken into account respectively.

Probing X/Y axis

Probing X/Y axis

Pass over

Probing Z axis















Application:

Please note:

Article-No.	Description	Shank	Length	Ball	Battery
001031200	Edge finder 3D	Ø12	approx.111 mm	Ø10	12V-Type 27A
001031600	Edge finder 3D	Ø16	approx.111 mm	Ø10	12V-Type 23A
001032000	Edge finder 3D	Ø20	approx.106 mm	Ø10	12V-Type 23A
001032500	Edge finder 3D	Ø25	approx. 116 mm	Ø10	12V-Type 23A
00103M200	Edge finder 3D	MK2	approx.146 mm	Ø10	12V-Type 27A

# Edge finder optical 3D in wooden case

Article-No.	Description	Shank	Length	Ball	Battery
001031299	Edge finder 3D	Ø12	approx.111 mm	Ø10	12V-Type 27A
001031699	Edge finder 3D	Ø16	approx.111 mm	Ø10	12V-Type 23A
001032099	Edge finder 3D	Ø20	approx.106 mm	Ø10	12V-Type 23A
001032599	Edge finder 3D	Ø25	approx.116 mm	Ø10	12V-Type 23A

precise. pioneering. worldwide.

 $\bigcirc$ 







# Probing accuracy <= 0.010 mm 🍯



# 3D version: **/** Probing in X, Y and Z •

For accurate zero point determination and bore centers to the spindle with an accuracy of probing smaller than 0.010 mm.

Protection against humidity is essential for the edge finder due to the built-in electronical components.

### **Delivery includes:**

Edge finder with serial number and test certificate in a plastic case.







23



# 3D precision probe



Scan me Product video

Our 3D precision probe is a higly precise measuring device which gives

out highly precise three dimensional probing results on metal-cutting

Within all three axis, the accuracy of probing is smaller than 0.005 µm.

Protection against humidity is essential for the edge finder due to the

3D precision probe with serial number and test certificate in a plastic

Shank

Ø20

Length

approx. 167 mm

rschort

Application:

machines.

Accurracy:

Please note:


**Delivery includes:** 

case (for clean storage).

Article-No. Description

001532000 3D precision probe

built-in electronical components.





### Edge finder optical & acoustic 2D / 3D



Article-No.	Description	Shank	Length	Ball	Battery
001122000	Edge finder 2D	Ø20	approx. 119 mm	Ø10	12V-Type 23A
001132000	Edge finder 3D	Ø20	approx.131 mm	Ø10	12V-Type 23A

003

 $\bigcirc$ 



24 \_\_\_\_\_ precise. pioneering. worldwide.

Battery

12V-Type 23A

Ball

Ø10

precise. pioneering. worldwide.







# Probing accuracy <= 0.010 mm 🧃

3D version: 📕 Probing in X, Y and Z 🧕



2D version: Probing in X and Y 🍯

### Application:

For accurate zero point determination and bore centers to the spindle with an accuracy of probing smaller than 0.010 mm.

When you reach the position, you hear an additional acoustic signal.

### Please note:

Protection against humidity is essential for the edge finder due to the built-in electronical components.

### **Delivery includes:**

Edge finder with serial number and test certificate in a plastic case.

25





TSCHORN<sup>®</sup>

## Edge finder optical 2D



### Application:

For accurate zero point determination and bore centers to the spindle with an accuracy of probing smaller than 0.010 mm.

### Please note:

Protection against humidity is essential for the edge finder due to the built-in electronical components.

### **Delivery includes:**

Edge finder with serial number and test certificate in a plastic case.

Article-No.	Description	Shank	Length	Ball	Battery
001021200	Edge finder 2D	Ø12	approx.99 mm	Ø10	12V-Type 27A
001021600	Edge finder 2D	Ø16	appeox. 99 mm	Ø10	12V-Type 23A
001022000	Edge finder 2D	Ø20	approx.94 mm	Ø10	12V-Type 23A
001022500	Edge finder 2D	Ø25	approx.104 mm	Ø10	12V-Type 23A
00102M200	Edge finder 2D	MK2	approx.133 mm	Ø10	12V-Type 27A



# Edge finder optical 2D in wooden case -

Article-No.	Description	Shank	Length	Ball	Battery	-
001021299	Edge finder 2D	Ø12	approx. 99 mm	Ø10	12V-Type 27A	6
001021699	Edge finder 2D	Ø16	approx.99 mm	Ø10	12V-Type 23A	
001022099	Edge finder 2D	Ø20	approx.94 mm	Ø10	12V-Type 23A	
001022599	Edge finder 2D	Ø25	approx.104 mm	Ø10	12V-Type 23A	1 80

### – Edge finder ECO –

### Version ECO

- low-cost
- Made in Germany
- no serial number
- no test certificate

Article-No.	Description	Shank	Length	Ball	Battery
0010216EP	Edge finder 2D	Ø16	approx.99 mm	Ø10	12V-Type 23A
0010220EP	Edge finder 2D	Ø20	approx.94 mm	Ø10	12V-Type 23A
	_				

### Spare parts

 $\bigcirc$ 

Article-No.	Description
0011Z6000	Spare battery 23A
0012Z6000	Spare battery 27A



– 26 \_\_\_\_\_ precise. pioneering. worldwide. -

precise. pioneering. worldwide.—





Volt
12V
12V





27