



SD PLUS CHUCK (AM TYPE)

SD 高精度夾頭刀柄 (AM型)




F Type Collet / F型 筒夾



Dual face contact
兩面接觸




Surface roughness
表面粗度



Run out accuracy
內孔偏擺度



Surface hardness
表面硬度



Carbonized depth
滲碳深度

Order Code 訂購編號	Range(d) 夾持範圍	L	L1	D	Min ⁺ G2.5 動態平衡	Nut 螺帽	Spanner 扳手
HSK40E-SD10-70AM	2~10	70	50	30	42,000	CN-SD10AM	30194-830
SD13-70AM	3~13	70	50	35	42,000	CN-SD13AM	30194-835
SD16-70AM	4~16	70	50	42	42,000	CN-SD16AM	30194-842
HSK50E-SD10-70AM	2~10	70	44	30	36,000	CN-SD10AM	30194-830
SD13-70AM	3~13	70	44	30	36,000	CN-SD13AM	30194-835
SD16-70AM	4~16	70	44	35	36,000	CN-SD16AM	30194-842

- Clamping nut design by circular cylinder. Bearing spanner must be used.
- Three types of collet to choose from (1) D type for gripping all type of tools. (2) E type for End mill. (3) F type for coolant supply.
- Bearing spanner and stop screw must be ordered separately.
- The circular nuts can be replaced with the hexagonal nuts.
- 全圓螺帽，必須使用軸承扳手。
- 筒夾有三種類別可選擇 (1) D型：可夾持任何刀具 (2) E型：銑刀專用 (3) F型：中心出水刀具使用。
- 軸承扳手及止動螺絲必須另外訂購。
- 全圓螺帽可以換成六角螺帽。

